

Assembly Instructions

Model:	RIDGE / RIDGE XR
Description: Trailerable Storage Cover	
Part Number:	99994-1806
Assembly Time:	15 Minutes

Before you begin, read these instructions and check that all parts are present.

Please note that Kawasaki cannot assume any responsibility for damage resulting from incorrect installation.

Kawasaki recommends that an authorized Kawasaki dealer fit all genuine accessories.

The following symbols indicate the information for proper installation and operation in this instruction.

AWARNING

WARNING indicates a hazardous situation that, if not avoided, could result in death or serious injury.

NOTE

Indicates a procedural step or work to be done.

NOTE indicates information that may help or guide you in the operation or service of the vehicle.

Indicates a procedural sub-step or how to do the work of the procedural step it follows. It also precedes the text of a NOTE.

Parts List				
No.	Component Name	Qty	Remark	
1	Storage Cover	1		

PARTS PHOTO



Installation Instructions

- Park the vehicle on level ground, set the parking brake, and turn off the ignition switch.
- Unfold the cover (1), loosen all straps and undo all clips.
- Locate the front of the cover which has the opening slits for tow straps.
- Place cover over vehicle and navigate it into place







Installation Instructions

• Loop rear straps through the lower a-arms then clip into cover and tighten straps.





• Pull cover down around rear wheels. Clip lower rear straps together and tighten.



Installation Instructions

• Connect under side front and rear straps and tighten.





 Congrats you have successfully installed your Genuine Kawasaki Storage Cover!

NOTE

: When using the cover during trailering of the vehicle, make sure all straps are tightened down completely and checked periodically.

While the cover is UV resistant, prolonged storage in direct sunlight is not recommended as it can fade and degrade the fabric over time.

Never apply any load to the cover while installed. Always remove any water, sand, or snow which may accumulate on it during storage.



In order to avoid risk of injury or damage, always face vehicle in forward position while carrying on truck or open trailer. Failure to comply may cause cover to detach from vehicle.

